## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (original) Device for fitting a brake device (4) to a snowboard (1), the brake device (4) comprising an active braking part in the form of a movable brake heel (10) that is flexibly joined to the base section (11) arranged on the snowboard (1), characterised in that the base section (11) and the snowboard (1) each comprises means (5, 8, 8', 9, 21, 24) that allow the base section (11) to slide to the intended position on the snowboard (1) and means (19, 25), which in a retaining manner, lock the base section (11) in place on the snowboard (1).

2. (original) Device in accordance with claim 1, characterised in that the means (5, 8, 8', 9, 21, 24) comprise a male and a female part respectively in the form of a continuous groove (5, 9, 24) and adjustable locking washers (8, 8', 21) in the groove.

3. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the means (19, 25) secure the locking washers (8, 8', 21) in the groove (5, 9, 24) through a clamping interaction with the base section (11) and the snowboard (1).

## BACKLUND, Jon U.S. National Phase of PCT/SE2003/001374

. -

- 4. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove (5, 9, 21, 24) extending at least past the entire length of one binding (3).
- 5. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove (5, 9, 21, 24) is arranged in conjunction with one of the long sides (2, 2') of the snowboard (1).
- 6. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove (5, 9) is designed with a cross-section exhibiting a shape and dimension corresponding to the locking washer (8, 8').
- 7. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove (5) comprises a continuous recess in the top of the snowboard.
- 8. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove is formed of a strip (9) glued or in some other way affixed to the top of the snowboard (1).

## BACKLUND, Jon U.S. National Phase of PCT/SE2003/001374

...

- 9. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the locking washers (8, 8') are arranged to the side of the base (11) of the brake device (4), which is facing the snowboard (1).
- 10. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the locking washers (8, 8') are arranged to the top of the snowboard (1).
- 11. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the groove (18, 24) is arranged to the base section (11) of the brake device (4) and comprises a cross-section corresponding to the shape of the locking washer (8, 8', 21).
- 12. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the locking washers (8, 8') comprise locking pins (13), the locking washers (8, 8') being mounted on the snowboard (1) with threaded inserts (17) arranged in depressions on the top of the snowboard (1).
- 13. (original) Device in accordance with claim 41\_12, characterised in that the threaded inserts (17) are arranged in pairs at a distance from each other at the front binding seen in the direction of riding.

## BACKLUND, Jon U.S. National Phase of PCT/SE2003/001374

- 14. (currently amended) Device in accordance with <u>claims 11 -\_ 12 claim 12</u>, characterised in that the threaded inserts (17) are arranged in pairs on both sides of the respective binding (3).
- 15. (currently amended) Device in accordance with any one of the previous claims claim 1, characterised in that the locking washer comprises a continuous runner (21) with an I-shaped cross-section arranged with its base (22') on the top of the snowboard (1).
- 16. (original) Device in accordance with with claim 14, characterised in that the base (11) of the brake device (4) is arranged with a continuous through groove (18) with a cross-section corresponding to the I-shaped runner (21).
- 17. (currently amended) Device in accordance with claims 7 and 14 claim 7, characterised in that the strip (9) and runner (21) comprise an elastic compliant material.
- 18. (original) Device in accordance with claim 16, characterised in that the strip comprises a polymeric material.